

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**


**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



**Figure 1.** 5% disodium tallowiminodipropionate with 2.25% phthalic acid at 25 and 50 degree C



**Figure 2:** Dynamic shear moduli measurements for samples with 5% disodium tallowiminodipropionate and 2.25% phthalic acid at 25 and 50 degree C



**Figure 3:** 5% disodium tallowiminodipropionate, 4% NH<sub>4</sub>Cl with different amount of phthalic acid (PA) at 25 C




Figure 4. Steady shear viscosity of different amount of oleamidopropyl betaine (BET-O) in presence of 3% KCl and 0.5% Phthalic Acid at 25 C




Figure 5. Dynamic shear moduli of different amount of oleamidopropyl betaine (BET-O) in presence of 3% KCl and 0.5% phthalic acid at 25°C.